

TECHNICAL FEATURES

Fuse matt

TECHNICAL FEATURES

TECHNICAL FEATURES UNGLAZED PORCELAIN STONWARE MOSAICS

CONFORMING TO EN 14411 ISO 13006 STANDARDS ANNEX G (GROUP BIA UGL EB ≤ 0,5%)

CARATTERISTICHE TECNICHE MOSAICO IN GRES PORCELLANATO NON SMALTATO Conformi a Norme EN 14411 ISO 13006 Appendice G (Gruppo BIA UGL Eb ≤ 0,5%)
TECHNISCHE EIGENSCHAFTEN FÜR MOSAIKE AUS UNGLASIERTEM FEINSTEINZEUG Gemäß den Europäischen Normen EN 14411 ISO 13006 Appendix G (Gruppe BIA UGL Eb ≤ 0,5%)
CARACTÉRISTIQUES TECHNIQUES DES MOSAÏQUES EN GRÈS CÉRAME NON ÉMAILLÉ Conformes aux Normes EN 14411 ISO 13006 Annexe G (Groupe BIA UGL Eb ≤ 0,5%)

Water absorption Assorbimento acqua EN ISO 10545-3	Compliant Conforme Eb ≤ 0,5%	Chemical resistance Resistenza agli agenti chimici EN ISO 10545-13	from ULA to ULB from UHA to UHB UA da ULA a ULB da UHA a UHB UA	Abrasion resistance Resistenza all'abrasione EN ISO 10545-6	Compliant Conforme 175 mm ³ max
Stain resistance Resistenza alle macchie EN ISO 10545-14	Class 5	Thermal expansion coefficient Coefficiente di dilatazione termica lineare EN ISO 10545-8	≤9 MK-1	Colors resistance to light Resistenza dei colori alla luce DIN 51094	No alteration after test Materiale inalterato dopo il test
Thermal shock resistance Resistenza agli sbalzi termici EN ISO 10545-9	Resistant Resistente	Frost resistance Resistenza al gelo EN ISO 10545-12	Resistant Resistente	Friction coefficient Coefficiente di attrito DIN EN 16165 Annex B ANSI A 137.1 (DCOF)	R10 matt >0,42

Fuse glossy

TECHNICAL FEATURES

TECHNICAL FEATURES GLAZED PORCELAIN STONWARE MOSAICS

CONFORMING TO EN 14411 ISO 13006 STANDARDS ANNEX G (GROUP BIA GL EB ≤ 0,5%)

CARATTERISTICHE TECNICHE MOSAICO IN GRES PORCELLANATO SMALTATO Conformi a Norme en 14411 ISO 13006 Appendice G (Gruppo BIA GL Eb ≤ 0,5%)
TECHNISCHE EIGENSCHAFTEN FÜR MOSAIKE AUS GLASIERTEM FEINSTEINZEUG Gemäß den Europäischen Normen EN 14411 ISO 13006 Appendix G (Gruppe BIA GL Eb ≤ 0,5%)
CARACTÉRISTIQUES TECHNIQUES DES MOSAÏQUES EN GRÈS CÉRAME ÉMAILLÉ Conformes aux Normes en 14411 ISO 13006 Annexe G (Groupe BIA GL Eb ≤ 0,5%)

Water absorption Assorbimento acqua EN ISO 10545-3	Compliant Conforme Eb ≤ 0,5%	Chemical resistance Resistenza agli agenti chimici EN ISO 10545-13	from GLA to GLB from GHA to GHB GA da GLA a GLB da GHA a GHB GA	Abrasion resistance Resistenza all'abrasione EN ISO 10545-7	class 0-5 from 2 to 3 da 2 a 3
Stain resistance Resistenza alle macchie EN ISO 10545-14	Class 5	Thermal expansion coefficient Coefficiente di dilatazione termica lineare EN ISO 10545-8	≤9 MK-1	Glaze crazing resistance Resistenza al cavillo EN ISO 10545-11	Resistant Resistente
Thermal shock resistance Resistenza agli sbalzi termici EN ISO 10545-9	Resistant Resistente	Frost resistance Resistenza al gelo EN ISO 10545-12	Resistant Resistente		