

TECHNICAL FEATURES | CARATTERISTICHE TECNICHE

TECHNICAL SPECIFICATIONS FOR WHITE-BODY WALL TILES

CONFORMING TO EN 14411 ISO 13006 STANDARDS APP. L GROUP BIII GL WITH EB > 10%

CARATTERISTICHE TECNICHE RIVESTIMENTI IN PASTA BIANCA Conformi a Norme EN 14411 ISO 13006 Appendice I Gruppo BIII GL con Eb > 10%
TECHNISCHE EIGENSCHAFTEN FÜR WANDFLIESEN AUS WEISSER MASSE Gemäß den Europäischen Normen EN 14411 ISO 13006 Appendix I Gruppe BIII GL mit Eb > 10%
CARACTÉRISTIQUES TECHNIQUES DES REVÊTEMENTS EN PÂTE BLANCHE Conformes aux normes EN 14411 ISO 13006 Annexe I Groupe BIII GL avec Eb > 10%

	TECHNICAL FEATURES CARATTERISTICHE TECNICHE TECHNISCHE DATEN CARACTÉRISTIQUES TECHNIQUES	TESTING METHOD METODICA DI PROVA PRÜFVERFAHREN NORME D'ESSAIS	TEST RESULTS VALORE PRODOTTO PRODUKT WERTE VALEUR PRODUIT
	Water absorption Assorbimento acqua Wasseraufnahme Absorption d'eau	UNI EN ISO 10545-3	AA>10% Group BIII
	Modulus of rupture Resistenza alla flessione Biegezugfestigkeit Résistance à la flexion	UNI EN ISO 10545-4	RM> 150kg/cm ²
	Crazing resistance Determinazione della resistenza al cavillo Glaserhaarrißbeständigkeit Résistance aux tréssailleures	UNI EN ISO 10545-11	Resistant Resistente Widerstandsfähig Résistant
	Chemical resistance Resistenza ai prodotti chimici Chemikalienbeständigkeit Résistance aux produits chimiques	UNI EN ISO 10545-14 UNI EN ISO 10545-13	Conforming Conforme Erfüllt Conforme



V1 PLAIN

PLEASE NOTE

The colours of the Reed collection feature a crackle glaze. However, this type of glaze requires special care when cleaning and may react negatively to acidic or harsh cleaning products. For both post-installation cleaning and routine maintenance, we recommend using pH-neutral cleaners. Avoid the use of limescale removers or acidic cleaning products, as they may dull the surface and affect its appearance.

NOTA BENE

I colori della collezione Reed sono realizzati con uno smalto craquelé. Tuttavia, questo tipo di smalto richiede particolari attenzioni nella pulizia e può reagire negativamente a prodotti acidi o detergenti aggressivi. Per la pulizia, sia subito dopo la posa che per la manutenzione quotidiana, è consigliato utilizzare detergenti neutri. È importante evitare l'uso di prodotti anticalcare, poiché potrebbero opacizzare la superficie e comprometterne l'aspetto.